
Firma: BIZ GROUP DOO BEOGRAD
Adresa: Kapetana Radiča Petrovića 32b
Telefon: 011 452 52 66, 060 452 52 66
Fax:
PIB: 111338015
E-mail: office@bizgroup.rs

MB s1200 Gigabyte H410M H V3 G10

Šifra: 22724
Kategorija prozivoda: Matične ploče za Intel socket
Proizvođač: GIGABYTE

Cena: 8.487,00 din.



Support for 10th Generation Intel® Core™ i9 processors/Intel® Core™ i7 processors/ Intel® Core™ i5 processors/Intel® Core™ i3 processors/Intel® Pentium® processors/ Intel® Celeron® processors in the LGA1200 package

L3 cache varies with CPU

Chipset
Intel® H510 Express Chipset

Memor

(Please refer to "CPU Support List" for more information.)

Intel® Core™ i9/i7 processors:
Support for DDR4 2933/2666/2400/2133 MHz memory modules

Intel® Core™ i5/i3/Pentium®/Celeron® processors:
Support for DDR4 2666/2400/2133 MHz memory modules

2 x DDR4 DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memory

Dual channel memory architecture

Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)

Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules

Support for Extreme Memory Profile (XMP) memory modules

(Please refer "Memory Support List" for more information.)

Onboard Graphics
Integrated Graphics Processor-Intel® HD Graphics support:

1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz

1 x HDMI port, supporting a maximum resolution of 4096x2160@30 Hz
* Support for HDMI 1.4 version and HDCP 2.3.

Maximum shared memory of 512 MB
(Graphics specifications may vary depending on CPU support.)

Audio
Realt

LAN
Gigabit Ethernet Chip (1 Gbps/100 Mbps)

Expans
1 x P
runni

Storage Interface
Chipset:

1 x M.2 connector (Socket 3, M key, type 2242/2260/2280 PCIe x4/x2 SSD support)

4 x SATA 6Gb/s connectors

USB

Chipset:

4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header)

6 x USB 2.0/1.1 ports (4 ports on the back panel, 2 ports available through the internal USB header)

Internal I/O Connectors

1 x 24-pin ATX main power connector

1 x 8-pin ATX 12V power connector

4 x SATA 6Gb/s connectors

1 x CPU fan header

1 x system fan header

1 x RGB LED strip header

1 x front panel header

1 x front panel audio header

1 x USB 3.2 Gen 1 header

1 x USB 2.0/1.1 header

1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)

1 x serial port header

1 x Clear CMOS jumper

*All fan headers are subject to support AIO_Pump, Pump and high performance fan with the capability of delivering up to 2A/12V @ 24W.

I/O Controller

iTE® I/O Controller Chip

BIOS

1 x 256 Mbit flash

Use of licensed AMI UEFI BIOS

PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Back P

1 x P

H/W M

Volta

Unique

Support for APP Center
* Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications.
@BIOS
Ambient LED
EasyTune
Fast Boot
Game Boost
ON/OFF Charge
Smart Backup
System Information Viewer

Support for Q-Flash

Support for Xpress Install

Bundled Software
Norton® Internet Security (OEM version)

Realtek® 8118 Gaming LAN Bandwidth Control Utility

Operat
Supp
64-bi

Form Factor
Micro ATX Form Factor; 22.6cm x 18.5cm

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.